SECTION 10 28 19 - AREZZO BYPASS BARN FRAMELESS SHOWER DOOR

PART 1 GENERAL

1.01 SUMMARY

- A. Section Includes:
 - 1. Frameless Bypass Door with Exposed Barn Style Rollers
- B. Related Sections:
 - 1. Section 05 50 00 (05500) Metal Fabrications
 - 2. Section 06 10 00 (06100) Rough Carpentry: Blocking
 - 3. Section 08 80 00 (08800) Glazing: Unframed mirrors, tub and shower glass
 - 4. Section 09 30 00 (09310) Tiling: Coordinate installation of accessories
 - 5. Section 10 21 13 (10165) Toilet Compartments: Coordinate installation of accessories

1.02 REFERENCES

- A. ASTM International Publications:
 - 1. ASTM C1048-85 (Glazing Materials)
- B. CPSC Standard
 - 1. CPSC 16CFR1201 11 (Glazing Materials)
- C. American National Standards Institute (ANSI)
 - 1. ANSI Z.97.1 (Tempered Glass)
- D. USFC Standard
 - 1. USFC DD-G-1403B (Tempered Glass)

1.03 SUBMITTALS

- A. Submit under provisions of Section 01 30 11:
- B. Product Data: Manufacturer's printed product data indicating compliance with specified requirements
- C. Shop Drawings: Submit elevations indicating overall dimensions, glass thickness, location and size of cut-outs, anchorage provisions and attachment methods.

1.04 QUALITY ASSURANCE:

- A. Manufacturer to have successfully provided similar fabrications to not less than five properties of comparable scope.
- B. Provide references
- 1.05 DELIVERY, STORAGE, AND HANDLING
 - SECTION 10 28 00 (10800) TOILET, BATH, AND LAUNDRY ACCESSORIESFRAMELESS SHOWER

 DOORS PAGE 1 -

- A. Packing and Shipping: Pack glass doors in wooden crates to minimize damage in shipping.
- B. Use Forklift to unload crates to prevent breakage
- C. Store crates to prevent physical damage or exposure to elements.
- D. Check for shipping damage immediately upon receipt and notify manufacturer immediately of any obvious damage.

1.06 WARRANTY

A. Mincey Marble Mfg., Inc shall provide a 5 year warranty from date of purchase on all shower door hardware if the shower door units are installed according to our specific installation instructions. (Glass is excluded from this warranty) Any part deemed to be defective during the warranty period will be provided at no charge. If the units are installed without adherence to our published instructions, the warranty will be null and void on all parts. This warranty does not cover polycarbonates or any claim arising from abuse, misuse, negligence, leakage, abrasives, accidents, improper installation or operation, or natural disasters.

PART 2 PRODUCTS

- 2.01 MANUFACTURERS
 - A. Preferred Manufacturer:
 - Mincey Marble Manufacturing Co. (770-532-0451)
 1940 New Harvest Road, Gainesville, GA 30507
 - B. Frameless Glass Model numbers
 - 1. ARZBP Two sliding bypass doors with sliding barn style shower door
 - C. Materials
 - 1. Tempered, clear glass with polished edges (3/8")
 - 2. Vertical wall jambs
 - Curb mounted door guide to guide sliding doors when opening and closing the doors
 - 4. 2 towel bars, 1 on each door, provided (stainless steel)
 - 5. Barn style rollers (stainless steel)
 - 6. Door rail, and door guide to support sliding doors
 - 7. Size: Refer to Drawings for width and height
 - D. Finish (choose one)
 - 1. Polished
 - 2. Brushed
 - E. Options (select or delete as required)
 - 1. Stainless steel (vertical wall jambs, door rail, door guide, & water diverter bar)
 - 2. Aluminum (vertical wall jambs, door rail, door guide, & water diverter bar)
 - SECTION 10 28 00 (10800) TOILET, BATH, AND LAUNDRY ACCESSORIESFRAMELESS SHOWER DOORS PAGE 2 -

PART 3 EXECUTION

3.01 PREPARATION

- A. Refer to shop drawings. Install wood blocking securely in the specified locations.
- B. Measure framed opening for glass & hardware (for example, frame for 60" opening, 54" opening, 48" opening etc.). Only one measurement needed for openings using same size pan/enclosure. Verify the openings are plumb and square.

3.02 INSTALLATION

- A. Install the frameless glass in accordance with manufacturer's printed instructions.
- B. Install true, plumb, and level, securely and rigidly anchored to substrate in accordance with manufacturer's instructions for each item and each type of substrate construction.
 - 1. Wood blocking shall be provided for the metal U-Channel as shown on Drawings.
 - 2. Strap metal is not acceptable for blocking.

END OF SECTION